



FEATURES

STRIKING OVERSCALED CYLINDRICAL HEADS GIVE AMBIENT ROOM LIGHT THROUGH THE MATT OPAL GLASS TOP DOMES AND DIRECTIONAL TASK LIGHT FROM BELOW. HEADS SWIVEL RIGHT/LEFT WITH A MECHANICAL STOP TO PREVENT OVER ROTATION. SUPPLIED FLAT-PACKED TO REDUCE PACKAGING VOLUME AND CARBON FOOTPRINT.

MATERIAL

STEEL AND GLASS WITH ACRYLIC DIFFUSERS


FINISH

BRUSHED BRASS (BRB)

CERTIFICATIONS

CE UK CA IP20

DIMENSIONS



FULL TECHNICAL SPECIFICATION

MATERIAL	STEEL AND GLASS WITH ACRYLIC DIFFUSERS	CABLE LENGTH	2000MM
FINISH	BRUSHED BRASS (BRB)	PLUG TYPE	UK 13 AMP
LAMPHOLDER TYPE	INTEGRAL LED	PLUG COLOUR	BLACK
INTEGRAL LIGHT SOURCE	4 X LED 3W 2700K	SWITCH TYPE	FOOT
COLOUR TEMPERATURE	2700K	DIMMABLE AS STANDARD?	BY REQUEST ONLY
WATTAGE (W) - INTEGRAL LED	12W	INSULATION RATING	CLASS I
CE	YES	IP RATING	IP20
UKCA	YES	BASE DIMENSIONS	280MM DIAMETER
UL	FOR UL PLEASE ENQUIRE.	NET PRODUCT WEIGHT	7KG
DRIVER LOCATION	INTEGRAL	OVERALL HEIGHT AS SHOWN	1500MM
CABLE TYPE	BLACK SILK-COVERED	OVERALL WIDTH AS SHOWN	280MM

FOR MORE INFORMATION ABOUT THIS PRODUCT:

Email: sales@chelsom.co.uk | Call: +44 (0)1253 831400

Chelsom Limited, Heritage House, Clifton Road, Blackpool, Lancashire FY4 4QA, United Kingdom

wordpress-700079-2614039.cloudwaysapps.com