



#### FEATURES

WARM LED LIGHT IS SOFTLY DIFFUSED THROUGH THE HEAVY MATT OPAL GLASS WHICH IS THREADED FOR SECURE ATTACHMENT. SQUARE SECTION TUBING CONTRASTS WITH D-ENDED BACKPLATE. THE LED READING LIGHT HAS AN INTEGRAL SWITCH. SUPPLIED FLAT-PACKED TO REDUCE PACKAGING VOLUME AND CARBON FOOTPRINT.

#### MATERIAL

STEEL AND GLASS

#### FINISH

SATIN BLACK (BL) WITH MATT OPAL GLASS

#### RECOMMENDED LAMP


1 X E14 4.5W LED 2700K PLUS 1 X LED 1W 2700K

#### CERTIFICATIONS

CE UK CA IP20

studio

#### DIMENSIONS



## FULL TECHNICAL SPECIFICATION

MATERIAL	STEEL AND GLASS	DRIVER LOCATION	INTEGRAL
FINISH	SATIN BLACK (BL) WITH MATT OPAL GLASS	SWITCH TYPE	PUSH
LAMPHOLDER TYPE	E14 AND INTEGRAL LED	DIMMABLE AS STANDARD?	BY REQUEST ONLY
RECOMMENDED LAMP	1 X E14 4.5W LED 2700K PLUS 1 X LED 1W 2700K	INSULATION RATING	CLASS I
COLOUR TEMPERATURE	2700K	IP RATING	IP20
MAX WATTAGE (RETROFIT)	30W	PROJECTION	195MM
WATTAGE (W) - INTEGRAL LED	1W	BACKPLATE DIMENSIONS	165 X 70MM
CE	YES	NET PRODUCT WEIGHT	1KG
UKCA	YES	OVERALL HEIGHT AS SHOWN	374MM
UL	FOR UL PLEASE ENQUIRE.	OVERALL WIDTH AS SHOWN	150MM

### FOR MORE INFORMATION ABOUT THIS PRODUCT:

Email: [sales@chelsom.co.uk](mailto:sales@chelsom.co.uk) | Call: +44 (0)1253 831400

Chelsom Limited, Heritage House, Clifton Road, Blackpool, Lancashire FY4 4QA, United Kingdom

[wordpress-700079-2614039.cloudwaysapps.com](https://wordpress-700079-2614039.cloudwaysapps.com)