

EST. 1947





FEATURES

STRIKING OVERSCALED CYLINDRICAL HEADS GIVE AMBIENT ROOM LIGHT THROUGH THE MATT OPAL GLASS TOP DOMES AND DIRECTIONAL TASK LIGHT FROM BELOW. HEADS SWIVEL RIGHT/LEFT WITH A MECHANICAL STOP TO PREVENT OVER ROTATION. SUPPLIED FLAT-PACKED TO REDUCE PACKAGING VOLUME AND CARBON FOOTPRINT.

MATERIAL


STEEL AND GLASS WITH ACRYLIC DIFFUSERS

FINISH

SATIN BLACK (BL)

CERTIFICATIONS

DIMENSIONS



FULL TECHNICAL SPECIFICATION

MATERIAL	STEEL AND GLASS WITH	CABLE LENGTH	2000MM
	ACRYLIC DIFFUSERS	PLUG TYPE	UK 13 AMP
FINISH	SATIN BLACK (BL)	PLUG COLOUR	BLACK
LAMPHOLDER TYPE	INTEGRAL LED		
INTEGRAL LIGHT SOURCE	4 X LED 3W 2700K	SWITCH TYPE	FOOT
INTEGRAL LIGHT SOURCE	4 X LED 3W 2700K	DIMMABLE AS STANDARD?	BY REQUEST ONLY
COLOUR TEMPERATURE	2700K	INCLUATION BATING	CL ACC I
WATTAGE (W) - INTEGRAL LED	12W	INSULATION RATING	CLASSI
WATTAGE (W) INTEGRAL ELD	12 **	IP RATING	IP20
CE	YES	BASE DIMENSIONS	280MM DIAMETER
UKCA	YES	BASE DIMENSIONS	2001VIIVI DIAWETEK
		NET PRODUCT WEIGHT	7KG
UL	FOR UL PLEASE ENQUIRE.	OVERALL HEIGHT AS SHOWN	1500MM
DRIVER LOCATION	INTEGRAL		
	DI 4 OV 011 V 00 VEDED	OVERALL WIDTH AS SHOWN	280MM
CABLE TYPE	BLACK SILK-COVERED		

FOR MORE INFORMATION ABOUT THIS PRODUCT:

Email: sales@chelsom.co.uk | Call: +44 (0)1253 831400