

EST. 1947





**DRIVER LOCATION** 

### **FEATURES**

ULTRA THIN METAL RING HAS WARM LED LIGHT LINING THE INSIDE WHICH IS SOFTENED BY WHITE ACRYLIC DIFFUSER. RING IS SUSPENDED ON ADJUSTABLE STRAINER WIRES WITH CONTROL GEAR HOUSED IN CEILING PLATE. THREE STANDARD SIZES (655MM; 855MM; AND 1155MM DIAMETER) ARE AVAILABLE AND CAN BE OFFERED IN VARIOUS CONFIGURATIONS. BESPOKE SHAPES AND SIZES CAN ALSO BE MANUFACTURED. PLEASE CONTACT OUR TEAMS TO DISCUSS FURTHER.

# **MATERIAL**


STEEL AND ACRYLIC DIFFUSER

#### **FINISH**

SATIN BLACK WITH OPAL ACRYLIC

# **CERTIFICATIONS**

### **DIMENSIONS**



# **FULL TECHNICAL SPECIFICATION**

MATERIAL	STEEL AND ACRYLIC	SUSPENSION TYPE	WIRE
	DIFFUSER	DIMMABLE AS STANDARD?	YES
FINISH	SATIN BLACK WITH OPAL ACRYLIC	DIMMING TYPE	1-10V
LAMPHOLDER TYPE	INTEGRAL LED	INSULATION RATING	CLASSI
INTEGRAL LIGHT SOURCE	LED 22W 2700K	IP RATING	IP20
COLOUR TEMPERATURE	2700K	MINIMUM DROP	500MM
WATTAGE (W) - INTEGRAL LED	22W	MAXIMUM DROP	CUSTOM
CE	YES	CEILING PLATE DIMENSIONS	275MM DIAMETER
UKCA	YES	NET PRODUCT WEIGHT	3KG
UL	FOR UL PLEASE ENQUIRE.	OVERALL WIDTH AS SHOWN	855MM

# FOR MORE INFORMATION ABOUT THIS PRODUCT:

INTEGRAL

Email: sales@chelsom.co.uk | Call: +44 (0)1253 831400