EST. 1947

UL





FEATURES

WARM LED LIGHT IS SOFTLY DIFFUSED THROUGH THE HEAVY MATT OPAL GLASS WHICH IS THREADED FOR SECURE ATTACHMENT. SQUARE SECTION TUBING CONTRASTS WITH D-ENDED BACKPLATE. THE LED READING LIGHT HAS AN INTEGRAL SWITCH. SUPPLIED FLAT-PACKED TO REDUCE PACKAGING VOLUME AND CARBON FOOTPRINT.

MATERIAL

STEEL AND GLASS

FINISH

SATIN BLACK (BL) WITH MATT OPAL GLASS

RECOMMENDED LAMP

1 X E14 4.5W LED 2700K PLUS 1 X LED 1W 2700K

CERTIFICATIONS



DIMENSIONS



FULL TECHNICAL SPECIFICATION

MATERIAL	STEEL AND GLASS	DRIVER LOCATION	INTEGRAL
FINISH	SATIN BLACK (BL) WITH	SWITCH TYPE	PUSH
	MATT OPAL GLASS	DIMMABLE AS STANDARD?	BY REQUEST ONLY
LAMPHOLDER TYPE	E14 AND INTEGRAL LED	INSULATION RATING	CLASSI
RECOMMENDED LAMP	1 X E14 4.5W LED 2700K PLUS 1 X LED 1W 2700K	IP RATING	IP20
COLOUR TEMPERATURE	2700K	PROJECTION	195MM
MAX WATTAGE (RETROFIT)	30W	BACKPLATE DIMENSIONS	165 X 70MM
WATTAGE (W) - INTEGRAL LED	1W	NET PRODUCT WEIGHT	1KG
CE	YES	OVERALL HEIGHT AS SHOWN	374MM
UKCA	YES	OVERALL WIDTH AS SHOWN	150MM

FOR MORE INFORMATION ABOUT THIS PRODUCT:

FOR UL PLEASE ENQUIRE.

Email: sales@chelsom.co.uk | Call: +44 (0)1253 831400