



FEATURES

HAS AN INTEGRAL LED LIGHT SOURCE AND A COLOUR CO-ORDINATED PUSH SWITCH IN BASE. OPAL ACRYLIC DIFFUSER GIVES GOOD DIFFUSED LIGHT.

MATERIAL

STEEL WITH ACRYLIC DIFFUSER

FINISH

POLISHED CHROME (C)

CERTIFICATIONS

CE UK CA IP20

DIMENSIONS



FULL TECHNICAL SPECIFICATION

MATERIAL	STEEL WITH ACRYLIC DIFFUSER	PLUG COLOUR	BLACK
FINISH	POLISHED CHROME (C)	SWITCH TYPE	PUSH
LAMPHOLDER TYPE	INTEGRAL LED	DIMMABLE AS STANDARD?	BY REQUEST ONLY
INTEGRAL LIGHT SOURCE	LED 12W 2700K	INSULATION RATING	CLASS I
COLOUR TEMPERATURE	2700K	IP RATING	IP20
WATTAGE (W) - INTEGRAL LED	12W	WIDTH	340
CE	YES	HEIGHT	410
UKCA	YES	PROJECTION	378MM
UL	FOR UL PLEASE ENQUIRE.	BASE DIMENSIONS	220MM DIAMETER
DRIVER LOCATION	INTEGRAL	NET PRODUCT WEIGHT	4.6KG
CABLE TYPE	BLACK SILK-COVERED	OVERALL HEIGHT AS SHOWN	420MM
CABLE LENGTH	2000MM	OVERALL WIDTH AS SHOWN	340MM
PLUG TYPE	UK 13 AMP		

FOR MORE INFORMATION ABOUT THIS PRODUCT:

Email: sales@chelsom.co.uk | Call: +44 (0)1253 831400

Chelsom Limited, Heritage House, Clifton Road, Blackpool, Lancashire FY4 4QA, United Kingdom

wordpress-700079-2614039.cloudwaysapps.com