CHELSOM
EST. 1947

LED KNURL
READING
LED/7/BRB




FEATURES
THE CYLINDRICAL HEAD HAS DETAILED KNURLING AND A BLACK ON/OFF PUSH SWITCH. THERE IS A DISCREET ROUND BACKPLATE WITH CONCEALED FIXINGS FOR REMOTE DRIVER LOCATION. PRICE INCLUDES REMOTE DRIVER.

MATERIAL
STEEL

FINISH
BRUSHED BRASS (BRB)

CERTIFICATIONS
CE UKCA UL IP20

DIMENSIONS



Cutout 25mm Ø


FULL TECHNICAL SPECIFICATION


MATERIAL	STEEL	**DIMMABLE AS STANDARD?**	BY REQUEST ONLY
FINISH	BRUSHED BRASS (BRB)	**INSULATION RATING**	CLASS II
LAMPHOLDER TYPE	INTEGRAL LED	**IP RATING**	IP20
INTEGRAL LIGHT SOURCE	LED 1W 2700K	**WIDTH**	45
COLOUR TEMPERATURE	2700K	**HEIGHT**	45
WATTAGE (W) - INTEGRAL LED	1W	**PROJECTION**	130MM
CE	YES	**BACKPLATE DIMENSIONS**	45MM DIAMETER
UKCA	YES	**CUTOUT DIMENSIONS**	25MM DIAMETER
UL	YES	**NET PRODUCT WEIGHT**	0.13KG
DRIVER LOCATION	REMOTE	**OVERALL HEIGHT AS SHOWN**	45MM
SWITCH TYPE	PUSH	**OVERALL WIDTH AS SHOWN**	45MM

FOR MORE INFORMATION ABOUT THIS PRODUCT:
Email: sales@chelsom.co.uk | Call: +44 (0)1253 831400
Chelsom Limited, Heritage House, Clifton Road, Blackpool, Lancashire FY4 4QA, United Kingdom
wordpress-700079-2614039.cloudwaysapps.com

CHELSOM

EST. 1947






LED/7

Revision A

CHELSOM


EST. 1947

FOLLOW THE NUMBERED ASSEMBLY SEQUENCE




SLR Information

This product contains a light source of Energy Efficiency Class E Regulation 2021 No. 1095



Non-replaceable light source



Control gear replaceable by qualified person

www.chelsom.co.uk