



#### FEATURES

INTERNAL INTEGRAL LED LIGHT SOURCE ALLOWS VERY SHALLOW SHADE FOR UNIQUE PROPORTIONS AND EXCELLENT DIFFUSED LIGHT DISTRIBUTION. COMPLETE WITH AN OFF WHITE FABRIC SHADE SECURED ON TOP WITH A DECORATIVE GROOVED DISC AND A DIMMER SWITCH. SUPPLIED FLAT-PACKED TO REDUCE PACKAGING VOLUME AND CARBON FOOTPRINT.

#### MATERIAL

STEEL AND FABRIC


#### FINISH

BRUSHED BRASS (BRB)

#### CERTIFICATIONS

CE UK CA IP20

#### DIMENSIONS



## FULL TECHNICAL SPECIFICATION

MATERIAL	STEEL AND FABRIC	PLUG TYPE	UK 13 AMP
FINISH	BRUSHED BRASS (BRB)	PLUG COLOUR	BLACK
LAMPHOLDER TYPE	INTEGRAL LED	SWITCH TYPE	FOOT DIMMER
INTEGRAL LIGHT SOURCE	LED 8W 2700K	DIMMABLE AS STANDARD?	YES
COLOUR TEMPERATURE	2700K	DIMMING TYPE	PHASE
WATTAGE (W) - INTEGRAL LED	8W	INSULATION RATING	CLASS I
CE	YES	IP RATING	IP20
UKCA	YES	BASE DIMENSIONS	300MM DIAMETER
UL	FOR UL PLEASE ENQUIRE	NET PRODUCT WEIGHT	10KG
DRIVER LOCATION	INTEGRAL	OVERALL HEIGHT WITH SHADE AS SHOWN	1575MM
CABLE TYPE	BLACK SILK-COVERED	OVERALL HEIGHT WITHOUT SHADE	1450MM
CABLE LENGTH	2000MM	OVERALL WIDTH WITH SHADE AS SHOWN	500MM

### FOR MORE INFORMATION ABOUT THIS PRODUCT:

Email: [sales@chelsom.co.uk](mailto:sales@chelsom.co.uk) | Call: +44 (0)1253 831400

Chelsom Limited, Heritage House, Clifton Road, Blackpool, Lancashire FY4 4QA, United Kingdom

[wordpress-700079-2614039.cloudwaysapps.com](https://wordpress-700079-2614039.cloudwaysapps.com)