



#### FEATURES

STRIKING OVERSCALED CYLINDRICAL HEAD GIVES AMBIENT ROOM LIGHT THROUGH THE MATT OPAL GLASS TOP DOME AND DIRECTIONAL TASK LIGHT FROM BELOW. HEAD SWIVELS RIGHT/LEFT WITH A MECHANICAL STOP TO PREVENT OVER ROTATION.

#### MATERIAL

STEEL AND GLASS WITH ACRYLIC DIFFUSER


#### FINISH

BRUSHED BRASS (BRB)

#### CERTIFICATIONS

CE UK CA IP20

#### DIMENSIONS



## FULL TECHNICAL SPECIFICATION

MATERIAL	STEEL AND GLASS WITH ACRYLIC DIFFUSER	CABLE LENGTH	2000MM
FINISH	BRUSHED BRASS (BRB)	PLUG TYPE	UK 13 AMP
LAMPHOLDER TYPE	INTEGRAL LED	PLUG COLOUR	BLACK
INTEGRAL LIGHT SOURCE	2 X LED 3W 2700K	SWITCH TYPE	IN LINE
COLOUR TEMPERATURE	2700K	DIMMABLE AS STANDARD?	BY REQUEST ONLY
WATTAGE (W) - INTEGRAL LED	6W	INSULATION RATING	CLASS I
CE	YES	IP RATING	IP20
UKCA	YES	BASE DIMENSIONS	200MM DIAMETER
UL	FOR UL PLEASE ENQUIRE.	NET PRODUCT WEIGHT	3.25KG
DRIVER LOCATION	INTEGRAL	OVERALL HEIGHT AS SHOWN	625MM
CABLE TYPE	BLACK SILK-COVERED	OVERALL WIDTH AS SHOWN	200MM

### FOR MORE INFORMATION ABOUT THIS PRODUCT:

Email: [sales@chelsom.co.uk](mailto:sales@chelsom.co.uk) | Call: +44 (0)1253 831400

Chelsom Limited, Heritage House, Clifton Road, Blackpool, Lancashire FY4 4QA, United Kingdom

[wordpress-700079-2614039.cloudwaysapps.com](https://wordpress-700079-2614039.cloudwaysapps.com)